

C122-E118-01EN

PRIMEQUEST 1000 SERIES

HBA blockage function

USER'S GUIDE

FOR SAFE OPERATION

HIGH RISK ACTIVITY

The Customer acknowledges and agrees that the Product is designed, developed and manufactured as contemplated for general use, including without limitation, general office use, personal use, household use, and ordinary industrial use, but is not designed, developed and manufactured as contemplated for use accompanying fatal risks or dangers that, unless extremely high safety is secured, could lead directly to death, personal injury, severe physical damage or other loss (hereinafter "High Safety Required Use"), including without limitation, nuclear reaction control in nuclear facility, aircraft flight control, air traffic control, mass transport control, medical life support system, missile launch control in weapon system. The Customer, shall not use the Product without securing the sufficient safety required for the High Safety Required Use. In addition, Fujitsu (or other affiliate's name) shall not be liable against the Customer and/or any third party for any claims or damages arising in connection with the High Safety Required Use of the Product.

TRADEMARK ACKNOWLEDGMENTS

Linux is a trademark or registered trademark of Linus Torvalds in the United States and other countries.

Red Hat is a trademarks or registered trademark of Red Hat, Inc. in the United States and other countries.

The contents of this manual shall not be reproduced in any way or form without the permission of Fujitsu Limited.

The contents of this manual may be revised without prior notice.

Copyright FUJITSU LIMITED 2010

Revision History

(1/1)

[illegible]

1 Section(s) with asterisk () refer to the previous edition when those were deleted.

Preface

Purpose of This Manual

This manual describes the functions and installation methods of HBA blockage driver supplied with the PRIMEQUEST-series machine.

Intended Readers

This manual is intended for system administrators responsible for system installation and operation.

Structure and Contents of This Manual

This manual is organized as described below:

Chapter 1 HBA Blockage Function

Provides an overview of the HBA blockage function and describes how to install and basically use this function.

Appendix A Command Reference

Explains usage of the HBA blockage command.

Appendix B Messages

Contains messages that are output by HBA blockage driver and command, explains the messages, and describes the appropriate actions to be taken.

Other Reference Manuals

The following manuals are provided for reference:

- *PRIMEQUEST 1000 Series General Description*
- *PRIMEQUEST 1000 Series Installation Manual*
- *PRIMEQUEST 1000 Series User Interface Operating Instructions*
- *PRIMEQUEST 1000 Series Administration Manual*
- *PRIMEQUEST 1000 Series Tool Reference*
- *PRIMEQUEST 1000 Series Message Reference*
- *PRIMEQUEST 1000 Series Glossary*

Contents

CHAPTER 1	HBA Blockage Function.....	1-1
1.1	Functional Overview	1-1
1.2	Installation Procedure.....	1-2
1.3	Register a blockading HBA.....	1-4
1.4	Change the blockading HBA.....	1-6
1.5	Notes concerning kdump service.....	1-6
1.6	Information for your support desk.....	1-6
APPENDIX A	Command Reference	A-1
A.1	HBA Blockage Function Command.....	A-1
A.2	Initial ram disk image edit command for kdump	A-3
APPENDIX B	Messages	B-1
B.1	fefpcl driver	B-1
B.2	fefpcl command	B-8
B.3	Initial ram disk image edit command for kdump.....	B-10

Illustrations

Figures

Figure 1.1 Configuration of the HBA blockage function	1-2
---	-----

CHAPTER 1 HBA Blockage Function

- | |
|---|
| <ul style="list-style-type: none">1.1 Functional Overview1.2 Installation Procedure1.3 Register a blockading HBA1.4 Change the blockading HBA1.5 Notes concerning kdump service1.6 Information for your support desk |
|---|

This chapter provides an overview of the HBA blockage function and describes how to install and basically use this function.

1.1 Functional Overview

The HBA blockage function achieves the following functions when OS panic has occurred.

- Guarantee of node-switching time. (case with a cluster-system, powered by PRIMECLUSTER)
- Notification of OS panic event. (to MMB(management feature))
- Stop request of software Watchdog. (to MMB)

When the HBA Blockage Function detects the OS panic, it blockades I/O request to HBA compulsorily. After that it notifies the OS panic event to MMB and PRIMECLUSTER. And it requests to stop the software Watchdog too.

A cluster-system powered by PRIMECLUSTER, which utilizes these functions for guarantee of node-switching time. When the OS panic occurred in a clustering node, cluster-system recovers the cluster-services in a very short time by these functions. (This function gives priority to the switching node over the dump collections.)

Figure 1.1 shows the configuration of the HBA blockage function.




Figure 1.1 Configuration of the HBA blockage function

The HBA blockage function consists of command part package and driver part package.

Please install both packages. (You should install these packages even if your system is not a cluster-system, because of notifying the OS panic event to MMB.)

And, if your system is a cluster-system, please register a blockading HBA.

1.2 Installation Procedure

Please install the packages of command part and driver part.

[RHEL5]

Command part: FJSVfefpcl-<OS version>-kmod-common-A.B.C-D.<arch>.rpm

Driver part: kmod-FJSVfefpcl-<OS version>-A.B.C-D.<arch>.rpm

<OS version> is characters that show the OS version. (ex. RHEL5)

A.B.C describes a version of the packages, and D describes a release number of the packages. (ex. 3.0.1-1)

README file for further details.

<arch> is CPU architecture. (ex. i686, x86_64)

■ Installation

1. Change to the super-user (root) privilege.

```
$ su
```

2. Install the rpm packages with the following command. They are upgraded if needed according to the situation:

```
# FJSVfefpcl/INSTALL.sh
```

3. Install PSA.

If you have not automatically installed hardware bundled-software by using ServerView Installation Manager (SVIM), then please refer to Appendix B of "PRIMEQUEST 1000 Series Installation Manual (C122-E107)" and install PSA. If PSA is already installed, you do not need to install PSA.

4. Reboot the system.

If you want to install two or more numbers of drivers, you have to reboot the system after all the install for each driver finished.

```
# /sbin/shutdown -r now
```

■ Uninstallation

1. Change to the super-user (root) privilege.

```
$ su
```

2. Uninstall the rpm packages with the following command.

```
# FJSVfefpcl/UNINSTALL.sh
```

3. Reboot the system.

If you want to uninstall two or more numbers of drivers, you have to reboot the system after all the uninstall for each driver finished.

```
# /sbin/shutdown -r now
```


1.3 Register a blockading HBA

In a cluster-system powered by PRIMECLUSTER, you must register a blockading HBA beforehand. Please register the all HBA which used to access the shared-disks in the cluster-system.

If the software (ETERNUS Multipath Driver or GR Multipath Driver, PRIMECLUSTER GDS) are worked in your system, you should finish the setting of these software. After that, you should execute this procedure.

You can register a blockading HBA by using the command (fepcl -a). If you want to know more functions about fepcl command, please refer to “Appendix A.1 HBA Blockage Function Command” of this manual.

Example)



This example shows the procedure for registration of HBA-1 and HBA-2 at Server-A.

You can register it by following command. This command argument is shared-disk (/dev/sdd) which is accessed by Server-A via HBA-1 and HBA-2.

```
# fepcl -a /dev/sdd
```

After that, you can confirm the registration.

```
# fepcl -l
/dev/sdd,/dev/sdd,grmpd 0000:ff:0a.0
/dev/sdd,/dev/sdd,grmpd 0000:ff:0b.0
```

* Please execute this registration procedure at the all server-node which constructs the cluster-system.

* If server works the software (ETERNUS Multipath Driver or GR Multipath Driver, PRIMECLUSTER GDS), two or more HBA may be registered to the server by specifying one shared-disk. (At this example, two HBA are registered by specifying one shared-disk.)

* The command (fepcl -l) shows a busID which is used as a key to identify HBA. You can confirm the number of registered HBA by counting the number of busID.

* You don't need to register the all shared-disks (devices). It is enough that the all blockading HBA has registered.

* It's not a problem even if you make duplicated definitions.

■ **Notes: When using a HBA with dual channel**

The HBA Blockage Function controls a HBA each PCI cards. So, it treats a HBA with dual channel as well as single channel.

1.4 Change the blockading HBA

You can change the blockading HBA by using `fefpcl` command. If you want to know more functions about `fefpcl` command, please refer to “Appendix A.1 HBA Blockage Function Command” of this manual.

1.5 Notes concerning `kdump` service

There are the following notes when using `kdump` service.

- `extra_modules` parameter can't be set in `/etc/kdump.conf`.
- If you started or restarted `kdump` service manually, you need to execute the following command successively, too.

```
# service y2lFJSVfefpcl-mkrd start
```

1.6 Information for your support desk

When you request the detail examination in case of the HBA Blockage Function, please present the files in the following directories with `fjsnap`'s output data. At that time, please don't remove it. (If you remove it, the HBA blockage Function may not work normally.)

- `/etc/opt/FJSVfefpcl`
- `/var/opt/FJSVfefpcl`
- The messages which was displayed on a console after a panic occurred.

APPENDIX A Command Reference

A.1 HBA Blockage Function Command

Syntax

```
fefpcl -a device-path...  
fefpcl -d label..  
fefpcl -c old-label new-label  
fefpcl -l | -r
```

Functions

This command controls the blockading HBA. It supports the following functions.

- Register the blockaging HBA which is indicated by device-path. (-a)
- Delete the blockaging HBA which is indicated by label. (-d)
- Change the label from old-label to new-label. (-c)
- Display the current settings (-l)
- Maintenance option (-r)

Please specify device-path in the following formats:

- /dev/sdX (X represents a disk unit identifier (an alphabetic character))
- /dev/sfdsk/*class-name*{r}dsk/*volume-name* (using PRIMECLUSTER GDS)
- /dev/disk/by-id/*device-name* (a device of by-id form)
- /dev/disk/by-path/*device-name* (a device of by-path form)

HBA Blockage Function controls the HBA by label. The device-path is set to label when it registered. You can change the label with -c option. Then, you should use the following character.

the first character	a-z A-Z 0-9 /
the other characters	a-z A-Z 0-9 / - _ . :

If the software (ETERNUS Multipath Driver or GR Multipath Driver, PRIMECLUSTER GDS) will be worked in your system, you should finish the setting of this software. After that, you should execute this command.

Options

-a Register the blockading HBA

The HBA is connected to device-path, which is registered as the blockading HBA. You do not need to register the all devices. And, multiple device-paths can be specified.

-d Delete the blockaging HBA

The HBA is indicated by label, which is deleted from the blockading HBA list. And, multiple labels can be specified.

-c Change the label from old-label to new-label.

-l Display the current blockading HBA list

<i>label,physical-devp[,grmpd] busID</i>
--

label : label name

physical-devp : the name of the physical device path of devp

[,grmpd] : state of use of the ETERNUS Multipath Driver
(prints "grmpd" if the driver is being used)

busID : an ID to identify PCI bus
(used as a key to identify HBA)

-r Maintenance option

This option is used at the HBA Blockade Function maintenance.

Note

At the following case, please re-register the blockading HBA.

- When the software (ETERNUS Multipath Driver or GR Multipath Driver, PRIMECLUSTER GDS) setting was changed.
- When a HBA was installed (or uninstalled) from the server by using PCI Hot Plug (PHP) or dynamic reconfiguration (DR).

End status

On success, 0 is returned.

On error, not 0 is returned.

A.2 Initial ram disk image edit command for kdump

Syntax

`service y21FJSVfefpcl-mkrd start`

Functions

This is the command to edit the initial ram disk image which is used by kdump service. Execute this command when you started or restarted kdump service manually.

Options

`start`

edit the initial ram disk image

End status

On success, 0 is returned.

On error, not 0 is returned.

APPENDIX B Messages

B.1 fefpcl driver

B.2 fefpcl command

B.3 Initial ram disk image edit command for kdump

Appendix B contains messages that are output by the drivers and commands covered by this manual, explains the messages, and describes the appropriate actions to be taken.

B.1 fefpcl driver

```
fefpcl: ERROR: could not register character device(%d).
```

Registration of the HBA blockage driver failed. Contact your support representative, and report the output message.

```
fefpcl: ERROR: could not register sysctl table.
```

Addition of the sysctl table for use by the HBA blockage driver failed. Contact your support representative, and report the output message.

```
fefpcl: ERROR: could not register callback function.
```

Registration of a callback function for use by the HBA blockage driver failed. Contact your support representative, and report the output message.

```
fefpcl: ERROR: callback function are overwritten(%p).
```

A callback function registered by the HBA blockage driver was overwritten. Contact your support representative, and report the output message.

```
fefpcl: ERROR: could not register entry point(%d).
```

An entry point that is necessary for the HBA blockage driver could not be registered. Contact your support representative, and report the output message.

fefpcl: ERROR: could not %s config space %04x:%02x:%02x.%x(%x:%x).

The PCI configuration space of the device mounted at %04x:%02x:%02x.%x cannot be accessed (access method: read or write). Contact your support representative, and report the output message.

fefpcl: ERROR: could not read config space %04x:%02x:%02x.%x(%x).

Data cannot be read from the PCI configuration space of the device mounted at %04x:%02x:%02x.%x. Contact your support representative, and report the output message.

fefpcl: ERROR: could not write config space %04x:%02x:%02x.%x(%x).

Data cannot be written to the PCI configuration space of the device mounted at %04x:%02x:%02x.%x. Contact your support representative, and report the output message.

fefpcl: ERROR: could not enter D3 state %04x:%02x:%02x.%x(%x).

The device that is mounted at %04x:%02x:%02x.%x cannot be placed in power management status D3. Contact your support representative, and report the output message.

fefpcl: ERROR: could not enter D0 state %04x:%02x:%02x.%x(%x).

The device that is mounted at %04x:%02x:%02x.%x cannot be placed in power management status D0. Contact your support representative, and report the output message.

fefpcl: ERROR: command timeout %04x:%02x:%02x.%x(%x).

A timeout occurred regarding a command issued to the device mounted at %04x:%02x:%02x.%x. Contact your support representative, and report the output message.

fefpcl: ERROR: command error %04x:%02x:%02x.%x(%x).

A command issued to the device mounted at %04x:%02x:%02x.%x ended with an error. Contact your support representative, and report the output message.

fefpcl: ERROR: could not stop a device %04x:%02x:%02x.%x(%x).

The function of the device mounted at %04x:%02x:%02x.%x cannot be stopped. Contact your support representative, and report the output message.

fefpcl: ERROR: stop device processing failed(%x).

Stop processing of the HBA function ended with an error. Contact your support representative, and report the output message.

fefpcl: INFO: loading driver - version %s

The HBA blockage driver was loaded. No corrective action is required.

fefpcl: INFO: unloading driver - version %s

The HBA blockage driver was unloaded. No corrective action is required.

fefpcl: INFO: execute alternative method.

The method used in stop processing of the HBA function was switched from operation with SHPC to operation with PCI PM. No corrective action is required.

fefpcl: INFO: initialization for stop device processing - %s:%d

Stop processing of the HBA function is being initialized. No corrective action is required.

fefpcl: INFO: stop device processing begins.

Stop processing of the HBA function started. No corrective action is required.

fefpcl: INFO: stop device processing is completed.

Stop processing of the HBA function is completed. No corrective action is required.

fefpcl: INFO: call psa function.

A PSA function was called. No corrective action is required.

fefpcl: INFO: stop device processing success.

Stop processing of the HBA function completed normally. No corrective action is required.

Psa_add_driver_to_ipmi Start

Psa_add_driver_to_ipmi Ret1

This message is displayed when HBA Blockage Function started. No action is required.

fefpcl I IP8150 sadump not exist

This message is displayed when sadump service is not started.

panicforpcl: ver. 1.0.0 initialize failed.

Loading panicforpcl that is the part of the fefpcl feature. Address the problem that is indicated by the messages that follows this message.

panicforpcl: create /proc/filename failed.

Creating /proc/<filename> failed. Confirm if the system memory is enough for the operation. If the memory is enough, contact your support representative with the output message and any other data for investigation.

panicforpcl: Sending ipmi message failed.

Issuing the IPMI message failed. Contact your support representative with the output message and any other data for investigation.

panicforpcl: IPMI code=XX, message.

Issuing the IPMI message failed. Contact your support representative with the output message and any other data for investigation.

panicforpcl: ver. 1.0.0 initialized.

panicforpcl that is the part of the fefpcl feature has been loaded. No corrective action is required.

panicforpcl: ver. 1.0.0 removed.

panicforpcl that is the part of the fefpcl feature has been unloaded. No corrective action is required.

**panicforpcl: Node Busy. Command could not be processed because
command processing resources are temporarily unavailable.**

If this message is output at the time of starting up of the FJSVfefpcl service, restart the service. If the same message is output again, or the message is output in any other case, contact your support representative with the output message and any other data for investigation.

panicforpcl: loading module-name failed.

Loading panicforpcl that is the part of the fefpcl feature failed. Confirm if the system install disk has any problem. If not, contact your support representative with the output message and any other data for investigation.

panicforpcl: Setting system status to dumping succeeded.

The status of the partition has been switched to "Dumping". No corrective action is required.

panicforpcl: Setting system status to halt succeeded.

The status of the partition has been switched to "Halt". No corrective action is required.

panicforpcl: Setting system status to halt succeeded.

Sending the IPMI message succeeded. No corrective action is required.

panicforpcl: Sending ipmi message failed.

Sending the IPMI message failed. Address the issue with the description that is output with this message.

panicforpcl: Setting system status to halt succeeded.

panicforpcl: SPMI(f0902000): IPMI: Bad SPMI legacy 0

panicforpcl: SPMI: Could not get SPMI table with ACPI

panicforpcl: Please wait for a few seconds.

Loading panicforpcl.ko module

panicforpcl: Setting system status to dumping.

panicforpcl: cannot get fefpcl_hook symbol.

These messages are printed by the HBA blockage feature while kdump is running.
No corrective action is required.

INFO: panicforpcl is already starting.

The FJSVfefpcl service has already been started. No corrective action is required.

ERROR: modprobe ipmi failed.

Loading the IPMI driver failed. Confirm if the system install disk has any problem.
If not, contact your support representative with the output message and any other data for investigation.

ERROR: modprobe panicforpcl failed.

Loading panicforpcl that is the part of the fefpcl feature failed. Confirm if the system install disk has any problem. If not, contact your support representative with the output message and any other data for investigation.

ERROR: kdump.conf is not found.

The kdump.conf file is not found. Set up the kdump feature correctly and restart the FJSVfefpcl service.

INFO: panicforpcl started.

The message is output when the FJSVfefpcl service has been started properly. No corrective action is required.

INFO: panicforpcl is already stopping.

The FJSVfefpcl service has already been stopped. No corrective action is required.

ERROR: rmmmod panicforpcl failed.

Unloading panicforpcl that is the part of the fefpcl feature failed. If the module has not already been unloaded, contact your support representative with the output message and any other data for investigation.

INFO: FJSVfefpcl stopped.

The FJSVfefpcl service has stopped properly. No corrective action is required.

B.2 fefpcl command

ERROR: must run as root.

The root privilege is required for execution. Execute the command with the root privilege (superuser privilege).

ERROR: initialization failed(%x).

Initialization of the HBA blockage driver application failed. Contact your support representative, and report the output message.

ERROR: unknown option -%c.

The specified option contains an error. Specify a supported option.

ERROR: unknown option character 0x%x.

The specified option contains an error. Specify a supported option.

ERROR: usage: fefpcl -a DEVICE-PATH

ERROR: or: fefpcl -d LABEL

ERROR: or: fefpcl -c OLD-LABEL NEW-LABEL

ERROR: or: fefpcl -l | -r

Show usage. Execute command according to this usage.

ERROR: invalid character used in NEW-LABEL.

ERROR: the first character is a-z A-Z 0-9 /

ERROR: the other characters are a-z A-Z 0-9 / - _ . :

Invalid character used in NEW-LABEL. Specify this character.

ERROR: illegal device-path %s.

Specified illegal device-path. Specify device-path according to the format.

ERROR: label %s is not found.

Label is not found in the blockading HBA list. Specify the label from the blockading HBA list.

ERROR: lack of resources(%x:%x).

There is a shortage of resources. Re-execute the same command later. If the same message is output, contact your support representative, and report the output message.

ERROR: %s: an input/output error has occurred(%x:%x).

An I/O error occurred. Contact your support representative, and report the output message.

ERROR: %s: failed to access file(%x:%x).

An error was detected during file access. Contact your support representative, and report the output message.

ERROR: there was a fatal error(%x).

A fatal error was detected. Contact your support representative, and report the output message.

B.3 Initial ram disk image edit command for kdump

```
Starting y21FJSVfefpcl-mkrd:[ OK ]
```

```
y21FJSVfefpcl-mkrd: started up
```

```
y21FJSVfefpcl-mkrd: started up (already modified)
```

```
y21FJSVfefpcl-mkrd: started up (Kdump is not operational)
```

The edit command ended normally.

```
Starting y21FJSVfefpcl-mkrd:[ FAILED ]
```

The edit command ended abnormally. Follow the action of the message displayed just before this message.

```
y21FJSVfefpcl-mkrd: Module fjpeghp.ko not found.
```

```
y21FJSVfefpcl-mkrd: Module panicforpcl.ko not found.
```

The internal module of HBA Blockage Function (fjpeghp.ko or panicforpcl.ko) is not found. Collect the output message and the data for investigation and please contact Fujitsu certified service engineer.

```
y21FJSVfefpcl-mkrd: Not found kdump initrd.
```

The initial ram disk image for kdump is not found. Restart kdump service and execute the initial ram disk image edit command for kdump (y21FJSVfefpcl-mkrd). If this message is still displayed after executing the above command, collect the output message and the data for investigation and please contact Fujitsu certified service engineer.

```
y21FJSVfefpcl-mkrd: Cannot define extra_modules parameter in  
/etc/kdump.conf.
```

extra_modules parameter can't be specified in /etc/kdump.conf. Execute the initial ram disk image edit command for kdump (y21FJSVfefpcl-mkrd) again after deleting extra_modules from /etc/kdump.conf.

```
y21FJSVfefpcl-mkrd: No disk space. Please clean /tmp directory.
```

There are not enough areas used as work area in /tmp. Execute the initial ram disk image edit command for kdump (y21FJSVfefpcl-mkrd) again after extending /tmp.

y21FJSVfefpcl-mkrd: Failed to restart the service of Kdump.

Restarting kdump service failed. Execute the initial ram disk image edit command for kdump (y21FJSVfefpcl-mkrd) again after reviewing the service setting of kdump.

FUJITSU